作業指導書編號:雕塑-P0604-4 版次:V1

REVISION DATE: 06/10/2010

ILFORD PHOTO

HARMAN technology Ltd

SAFETY DATA SHEET Ilfotec LC29 Developer

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Ilfotec LC29 Developer

PRODUCT NO. 1131811 **INTERNAL ID** 10017

APPLICATION Photographic Developer Solution

SUPPLIER Distributors

UK: HARMAN technology Ltd, Ilford Way, Mobberley, Cheshire, WA16 7JL, UK Tel: 01565 650000, Fax:

01565 872734.

(http://www.harmantechnology.com) Australia: CR Kennedy & Co Pty Ltd, 663 Chapel Street, South Yarra, Victoria 3141, Australia. Tel: 03 9823

1555, Fax: 03 9827 7216

CONTACT PERSON UK: HS&E Advisor Dr Trevor Rhodes Tel: +44(0)1565 650000, email:

trevor.rhodes@harmantechnology.com Australia: Contact Distributor (http://www.crkennedy.com.au) Tel

+61 (0)3 9823 1555

EMERGENCY TELEPHONE Swiss Toxicological Information Centre (24 hours) Tel: +41 (0)1 251 5151, Fax: +41 (0)1 252 8833

E-mail: stic@access.ch, Internet: www.toxi.ch

CONTAINER SIZE 500ml

2 HAZARDS IDENTIFICATION

Harmful if swallowed. Irritating to skin. Risk of serious damage to eyes. May cause sensitisation by skin contact. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure if swallowed. Very toxic to aquatic organisms. Possible risk of irreversible effects.

CLASSIFICATION (1999/45) Xn;R22, R48/22. Carc. Cat. 3;R40, Muta Cat. 3;R68. Xi;R38, R41. R43. N;R50.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)	
1-Phenyl-4-methyl-3-pyrazolidone	220-180-6	2654-57-1	< 1	Xn;R22,R43.	
2,2'-OXYBISETHANOL	203-872-2	111-46-6	5-10%	Xn;R22	
DIETHANOLAMINE	203-868-0	111-42-2	10-30%	Xn;R22,R48/22 Xi;R38,R41	
Diethanolamine Bisulphite	263-968-5	63149-47-3	10-30%	Xn;R21/22. Xi;R36/38. R31.	
Diethanolamine Hydrobromide		28129-21-7	1-5%	Xn;R22,R48/22. Xi;R38,R41.	
Diethylenetriamine Pentaacetic Acid Na5	205-391-3	140-01-2	1-5%	Xi;R36/38.	
HYDROQUINONE	204-617-8	123-31-9	5-10%	Carc. Cat. 3;R40 Muta. Cat. 3;R68 Xn;R22 R43 Xi;R41 N;R50	

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Hazardous according to the criteria of Worksafe Australia

4 FIRST-AID MEASURES

INHALATION

Unlikely route of exposure as the product does not contain volatile substances. Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION

Remove victim immediately from source of exposure. Rinse mouth thoroughly. Drink a few glasses of water or milk. DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Contact physician if irritation continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS

No unusual fire or explosion hazards noted.

SPECIFIC HAZARDS

When heated and in case of fire, harmful vapours/gases may be formed.

PROTECTIVE MEASURES IN FIRE

Use protective equipment appropriate for surrounding materials. Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Avoid contact with skin and eyes. Provide adequate ventilation. For personal protection, see section 8.

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground. The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

SPILL CLEAN UP METHODS

For waste disposal, see section 13. Wear necessary protective equipment. Small quantities may be flushed to drains with plenty of water. Absorb in vermiculite, dry sand or earth and place into containers. Wash contaminated area with water. Prevent discharge of larger quantity to drain.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Provide good ventilation. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Read and follow manufacturer's recommendations

STORAGE PRECAUTIONS

Store in closed original container in a dry place. Store above freezing. Store under well-ventilated conditions at a temperature below 25°C.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
2,2'-OXYBISETHANOL	WEL	23 ppm	101 mg/m3			
HYDROQUINONE	WEL		0.5 mg/m3			

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT





ENGINEERING MEASURES

Provide adequate ventilation. Must not be handled in confined space without sufficient ventilation.

RESPIRATORY EQUIPMENT

Respiratory protection not required.

HAND PROTECTION

Use protective gloves. Nitrile gloves are recommended.

EYE PROTECTION

Use eye protection.

OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Viscous Liquid

COLOUR Clear Colourless to pale yellow

ODOUR No characteristic odour.

SOLUBILITY 100% Soluble in water.

BOILING POINT (°C) >100 760 mm Hg RELATIVE DENSITY 1.07 20

pH-VALUE, CONC. SOLUTION 9.4

10 STABILITY AND REACTIVITY

STABILITY

Stable under the prescribed storage conditions. No particular stability concerns.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time. Avoid contact with acids.

HAZARDOUS POLYMERISATION

Will not polymerise.

MATERIALS TO AVOID

Strong acids. Avoid contact with other photographic solutions and/or cleaning compounds.

HAZARDOUS DECOMPOSITION PRODUCTS

When heated, toxic and corrosive vapours/gases may be formed. Fire or high temperatures create: Sulphurous gases (SOx). Ammonia or amines.

11 TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

This chemical formulation has not been tested for health effects. Exposure effects listed are based on existing health data for the individual components that comprise the mixture.

INHALATION

May cause irritation to the respiratory system.

INGESTION

Harmful if swallowed. May cause discomfort if swallowed.

SKIN CONTACT

Irritating to skin. May cause sensitisation by skin contact. May cause allergic contact eczema.

EYE CONTACT

Irritation of eyes and mucous membranes. Repeated exposure may cause chronic eye irritation.

HEALTH WARNINGS

Prolonged or repeated exposure may cause severe irritation. May cause skin irritation/eczema. May cause sensitisation by skin contact. Irritating to eyes.

Spray and vapour in the eyes may cause irritation and smarting.

May cause allergy. May cause hypersensitivity.

OTHER HEALTH EFFECTS

Hydroquinone: Carcinogen Category 3. Mutagen Category 3. ACGIH A3 IARC 3 IARC Animal Carcinogen List. IARC Int. Agency for Cancer Research.

ROUTE OF ENTRY

Skin and/or eye contact. Ingestion.

MEDICAL CONSIDERATIONS

May aggravate existing: Skin disorders and allergies. Pre-existing eye problems.

 Name
 DIETHANOLAMINE

 Toxic Dose 1 - LD 50
 620 mg/kg (oral rat)

 Name
 HYDROQUINONE

 Toxic Dose 1 - LD 50
 320 mg/kg (oral rat)

 Toxic Dose 2 - LD 50
 >900 mg/kg (skn-rat)

 Name
 2,2'-OXYBISETHANOL

 Toxic Dose 1 - LD 50
 12,600 mg/kg (oral rat)

Name Diethylenetriamine Pentaacetic Acid Na5

Toxic Dose 1 - LD 50 >4000 mg/kg (oral rat)

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product contains a substance which is very toxic to aquatic organisms.

MOBILITY

The product is soluble in water.

BIOACCUMULATION

No data available on bioaccumulation.

DEGRADABILITY

No data available.

Name DIETHANOLAMINE

LC 50, 96 Hrs, FISH mg/l >100 mg/L (Fathead Minnow)

Name HYDROQUINONE

LC 50, 96 Hrs, FISH mg/l 0.10-0.18 (Fathead Minnow)

EC 50, 48 Hrs, DAPHNIA, mg/l 0.05 IC 50, 72 Hrs, ALGAE, mg/l 1.0

Name 2,2'-OXYBISETHANOL

LC 50, 96 Hrs, FISH mg/l >100 EC 50, 48 Hrs, DAPHNIA, mg/l 0.3 - 1

Name Diethylenetriamine Pentaacetic Acid Na5

LC 50, 96 Hrs, FISH mg/l >1000 (lepomis macrochirus)
EC 50, 48 Hrs, DAPHNIA, mg/l >500 (daphnia magna)

13 DISPOSAL CONSIDERATIONS

GENERAL INFORMATION

The disposal process for this product when it becomes waste, depends largely upon how much (volume) waste is generated, where the waste is generated (location) and by whom (whether in a professional or amateur or other capacity). Therefore only outline guidance can be provided. For detailed guidance and specialist advice on the disposal of this product when it becomes waste, please visit the COPPICE web site at http://www.pic.uk.net/coppice/index.htm. The information is relevant to both professional and amateur users.

DISPOSAL METHODS

Used, diluted, and spent solutions may be allowed to be discharged to sanitary sewer by permit IF allowed by local regulations. Consult your local authority for advice. Waste may have to be pre-treated before discharge. Consult local authorities before discharging any waste to sewer. Do not discharge to septic system. Waste that cannot be discharged to sewer may have to handled by a licensed hazardous waste contractor.

14 TRANSPORT INFORMATION

GENERAL

LIMITED QUANTITY EXEMPTION



PROPER SHIPPING NAME UN3082, Environmentally hazardous substance, liquid, n.o.s. (contains hydroquinone).

UN NO. ROAD3082ADR CLASS NO.9 (M6)ADR CLASSClass 9: Other dangerousADR PACK GROUPIII

substances.

TUNNEL RESTRICTION CODE (E) HAZARD NO. (ADR) 90 Environmentally hazardous

substance; miscellaneous dangerous substances.

ADR LABEL NO. 9 RID CLASS NO. **RID PACK GROUP** Ш UN NO. SEA 3082 IMDG CLASS 9 IMDG PACK GR. Ш **EMS** UN NO. AIR F-A, S-F 3082 AIR CLASS AIR PACK GR. Ш

15 REGULATORY INFORMATION

LABELLING







Dangerous for the environment

CONTAINS DIETHANOLAMINE

HYDROQUINONE

RISK PHRASES

R22 Harmful if swallowed.
R38 Irritating to skin.

R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.

R50 Very toxic to aquatic organisms.
R68 Possible risk of irreversible effects.

SAFETY PHRASES

S2 Keep out of the reach of children.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

S46 If swallowed, seek medical advice immediately and show this container or label.
S61 Avoid release to the environment. Refer to special instructions/safety data sheets.

S64 If swallowed, rinse mouth with water (only if the person is conscious).

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Worksafe Australia NOHSC 2012: Labelling of workplace substances. Australian Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP). Australian Approved Criteria for Classifying Hazardous Substances (NOHSC 1008). Australian List of Designated Hazardous Substances (NOHSC 10005). Australian National Code of Practice for the Preparation of Material safety Data Sheets (NOHSC 2011)

REVISION DATE: 06/10/2010

Ilfotec LC29 Developer

GUIDANCE NOTES

CHIP for everyone HSG(108).

NATIONAL REGULATIONS

Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments. Workplace Exposure Limits 2007 (EH40) The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 No 716

16 OTHER INFORMATION

GENERAL INFORMATION

HARMAN technology Ltd believe the information and recommendations contained herein are based on correct and factual data. However, no express or implied guarantee or warranty of any kind is made with respect to this information. Use this information only to supplement other information you have gathered and then make an independent determination about the completeness and suitability of all information to ensure the proper use and disposal of this product and the health and safety of employees and customers.

INFORMATION SOURCES

European Photographic Chemical Industry Code of Practice For Classification And Labelling Material Safety Data Sheet, Misc. manufacturers. Dangerous Properties of Industrial Chemicals, 6.edition, N.Sax, 1984.

ISSUED BY

HS&E Advisor Dr Trevor Rhodes Tel: +44(0)1565 650000, email: trevor.rhodes@harmantechnology.com

REVISION DATE 06/10/2010

REV. NO./REPL. SDS

GENERATED

RISK PHRASES IN FULL

R31 Contact with acids liberates toxic gas.

R22 Harmful if swallowed.

R21/22 Harmful in contact with skin and if swallowed.

R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.

R36/38 Irritating to eyes and skin.

R38 Irritating to skin.

R40 Limited evidence of a carcinogenic effect.
R43 May cause sensitisation by skin contact.
R68 Possible risk of irreversible effects.
R41 Risk of serious damage to eyes.
R50 Very toxic to aquatic organisms.